

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number  
WO 2004/028839 A1

(51) International Patent Classification?: B60G 17/015

(21) International Application Number:  
PCT/NO2003/000324

(22) International Filing Date:  
24 September 2003 (24.09.2003)

(25) Filing Language: Norwegian

(26) Publication Language: English

(30) Priority Data:  
20024604 25 September 2002 (25.09.2002) NO

(71) Applicant (for all designated States except US): KONGS-  
BERG AUTOMOTIVE ASA [NO/NO]; P.O. Box 62,  
N-3602 Kongsberg (NO).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BJØRKGÅRD, Sven  
[NO/NO]; Rådmann Friis vei 41, N-3610 Kongsberg (NO).

(74) Agent: ONSAGERS AS; P.O. Box 6963 St. Olavs plass,  
N-0130 OSLO (NO).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,  
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,  
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,  
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,  
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: A SYSTEM FOR SENSING LEVEL CHANGE IN VEHICLES



(57) Abstract: A system for sensing relative position between chassis (5a, 5b) and axle (3) on a vehicle, which vehicle is provided with a so-called V-rod (1) mounted between the chassis (5a, 5b) and the axle (3) where the pointed end of the V is connected by a ball joint (2) to the axle (3) of the vehicle and the opposite ends (1a, 1b) of the V-rod (1) are connected to the chassis (5a, 5b) of the vehicle, which ball joint (2) comprises a partly ball-shaped body (8) permanently fixed to the axle or the v-rod, encircled by a complementarily shaped collar (9) arranged round the whole or parts of the ball-shaped body (8) which ball joint (2) is covered by a cap or housing. The system is characterised in that on the ball (8) or in connection with the housing in the ball joint there are mounted a sensor (6) and an identification area (7) which is detected by the sensor (6) respectively, which identification area (7) is provided with information for registering position in at least one direction and that the sensor (6) registers the position of the identification area (7) in at least one direction.

BEST AVAILABLE COPY

WO 2004/028839 A1